

| |
|----------------|
| Catalog Number |
| Notes |
| Type |

FEATURES & SPECIFICATIONS

INTENDED USE

Provides protection from vandalism for units and remote heads.

CONSTRUCTION

9-gauge steel rod construction.

Mounts securely to wall.

Note: ELA WG1 and ELA WG3 ships standard with pan head 14 x 1-1/2" screws.


Actual performance may differ as a result of end-user environment and application. Specifications subject to change without notice.

See Compatibility And Ordering Information next page.


Unit Accessories

ELA WG


WIREGUARD




ELA WG1



ELA WG3



ELA WGEXE



ELA WGLG
(20"H x 21"W x 18"D)
(discontinued, 1/14/2021)

Shipping weight:

| | |
|------------|--------------------|
| ELA WG1: | 2.8 lbs (1.27 kgs) |
| ELA WG2: | 2.8 lbs (1.27 kgs) |
| ELA WG3: | 2.8 lbs (1.27 kgs) |
| ELA WG2M: | 2.0 lbs (0.91 kg) |
| ELA WG4/8: | 6.1 lbs (2.77 kgs) |
| ELA WGEXT: | 8.0 lbs (3.63 kg) |
| ELA WGEXE: | 2.0 lbs (0.91 kg) |
| ELA WGLG: | 8.0 lbs (3.63 kg) |

ELA WG Wireguard

COMPATIBILITY AND ORDERING INFORMATION

| | 186MTH ELA WG1 (13 3/4"H x 15 1/4"W x 6"D) | 240144 ELA WG2 (14-3/8"H x 15-1/8"W x 8-5/8"D) | 186MTJ ELA WG3 (13 3/4"H x 30 5/8"W x 6"D) | 254016 ELA WG2M (15"H x 21-1/4"W x 12"D) | 240009 ELA WG4/8 (22-15/16"H x 22-1/8"W x 10"D) | 282514 ELA WGEXT (11"H x 18"W x 11"D) | 283279 ELA WGEXE (11"H x 15"W x 4-3/4"D) |
|--|--|--|--|--|---|---|--|
| LQM - Back Mount | ■ | | | | | | |
| LQM - Top Mount | | | | | | ■ | |
| LQM - End Mount | | | | | | | ■ |
| LE - Back Mount | ■ | | | | | | |
| LE - Top Mount | | | | | | ■ | |
| LE - End Mount | | | | | | | ■ |
| LHQM (5.4W incand. head) - Back Mount ¹ | | | ■ | | | | |
| LHQM LP06VS - Back Mount | | | ■ | | | | |
| ELM/ELM2 ¹ | ■ | | | | | | |
| ELM6-12 ¹ | | | | ■ | | | |
| ELM6 LED ¹ | ■ | | | | | | |
| IND 18W-100W ¹ | | | | ■ | | | |
| INDX ¹ | | | | | ■ | | |
| All Two Remote Heads | | ■ | | | | | |
| All Single Remote Heads | | ■ | | | | | |
| ELT16,24,36 | | ■ | | | | | |
| ELT 50 w/out-option | | ■ | | | | | |
| ELT 50 w/option & 125,180,275 | | | | | ■ | | |
| EC_LED (R/G) - Back Mount | | | ■ | | | | |
| ECC (R/G) Back Mount | | | ■ | ■ | | | |
| EX_LED (R/G) Back Mount | ■ | | | | | | |
| EX_LED (R/G) Top Mount | | | | | | ■ | |
| EX_LED (R/G) End Mount | | | | | | | ■ |
| ELM2 LED ¹ | ■ | | | | | | |
| LHQM LED | | | ■ | ■ | | | |
| ELA Q LED | ■ | | | | | | |
| LQC Back Mount | ■ | | | | | | |
| LQC Top Mount | | | | | | ■ | |
| LQC End Mount | | | | | | | ■ |
| LE NY Top Mount | | | | | | ■ | |
| LE NY End Mount | | | | | | | ■ |
| LE NY Back Mount | ■ | | | | | | |
| LXC Back Mount | ■ | | | | | | |
| LX NY Back Mount | ■ | | | | | | |
| D-Series Top | | | | | | ■ | |
| D-Series Back | ■ | | | | | | |
| ELT 618 NY | | | | ■ | | | |
| ELT627-1250NY | | | | | ■ | | |
| ELTC (all sizes) | | | | | ■ | | |
| TLE Back Mount | ■ | | | | | | |
| TLE Top Mount | | | | | | ■ | |
| TLE End Mount | | | | | | | ■ |
| WLTE (back mount) | ■ | | | | | | |
| WLTU | | ■ | | | | | |
| WLTU MR | ■ | | | | | | |
| EU2 LED ¹ | ■ | | | | | | |
| EU2 ¹ | | | ■ | | | | |
| EU2C Back mount | ■ | | | | | | |
| EU2L Back mount | ■ | | | | | | |
| ELM2L/ELM2LF/ELM4L/ELM6L | ■ | | | | | | |
| ECRM back mount | | | ■ | | | | |
| EXRM back mount | ■ | | | | | | |

Notes

1 Fixture series obsolete, wireguard still available.