


ACL3/0-2/0

by CMC

Catalog ID: ACL3/0-2/0



Aluminum Common Die Splice Connectors

- For splicing aluminum or copper conductors when joined in limited or loop-tension applications such as pole jumpers and service entrances
- Connectors are pre-filled and plugged with electrical joint compound
- Also useful in underground secondaries
- Marked with catalog number, conductor size, and die references
- Material: Aluminum

Product Details

General

Die Size	<ul style="list-style-type: none"> • Kearney K840 • Burndy 249 • EEI 11A • T&B TX • T&B 76 • VC6 (all)
Material	Aluminum
UPC	192663117949

Dimensions

Length	4 in
--------	------

Conductor Related

Conductor - ACSR Cmpt Size A	4/0 AWG
Conductor - ACSR Cmpt Size B	1/0 AWG & 2/0 AWG
Conductor - AL Str Size A	3/0 AWG
Conductor - AL Str Size B	1/0 AWG

Conductor - Copper Str Compact Size A	4/0 AWG
Conductor - Copper Str Compact Size B	1/0 AWG & 2/0 AWG
Conductor - Copper Str Size A	3/0 AWG
Conductor - Copper Str Size B	1/0 AWG

Certifications and Compliance

Industry Standard(s)	ANSI C119.4
----------------------	-------------



CONNECTOR MANUFACTURING COMPANY
3501 Symmes Road
Hamilton, Ohio 45015 - 1369
513 - 860 - 4455(Press 2 for Customer Service and Sales)
To email customer Service: jrex@cmclugs.com

