

Abotar 8101-8™

Fill, Patch, and Resurface Asphalt Surfaces



Applications:

Abotar 8101-8™ is a versatile tar-epoxy that provides controllable flexibility when filling, resurfacing, and patching asphalt. This is useful when a soft layer (1 Part A / 2 Parts B, neat or blended with aggregate) is followed by applications of harder layers (1 Part A / 1 Part B). Abotar 8101-8 is an excellent choice for use on ship decks, runways, parking garages, commercial and industrial floors, pipes, driveways, sidewalks, and roofs. It is weather and waterproof, and resists acids, alkalis, and fuels. Sand or other aggregate can be added to expand volume and enhance the coefficient of thermal expansion (important when patching large areas). Apply Abotar 8101-8 with a brush, roller, or by pouring.

Features and Benefits:

- Two part, tar-epoxy resurfacing compound
- Ideal for asphalt or blacktop surfaces
- Corrosion resistant
- Resin and hardener can be mixed in varying ratios to increase or minimize flexibility (1 volume Part A / 0.5 - 2 volumes Part B)
- Weather and water resistant
- Acid, alkali and fuel resistant

Manufactured By:



Technical Characteristics:

- Weight/gallon: Part A - 9.2 lb / 4.2 Kg; Part B - 9.1 lb / 4.1 Kg
- Induction Period: = > 15 minutes
- Pot life: = < 1 hour
- Hardening time: 2-12 hours at 75° F (24° C); faster with heating
- Color: Part A - Clear; Part B - Black
- 100% Solids
- Viscosity: 500 - 2000 cPs; 5 - 20 poises
- Coverage: Approximately 160 sq. ft. x 10 mil per gallon

Hardness, 2/1 ratio	75 Shore D (approx.)
Hardness, 1/1 ratio	65 Shore D (approx.)
Hardness, 1/2 ratio	32 Shore D (approx.)

**The above information is based upon laboratory testing. Users are urged to test the product under their own conditions.*

Instructions:

- This is a two part product: A (resin) and B (hardener).
- Mix Parts A and B in the ratio specified on the labels for the desired flexibility.
- Apply mixture to clean, dry, surface free of contaminants, oil, grease, wax, and debris, with roller or brush.
- If necessary, add sand or aggregate as needed.

Packaging:

- 2 Quart Kit
- 2 Gallon Kit
- 10 Gallon Kit

LIMITED WARRANTY

As uses and applications of this product are beyond the control of the manufacturer, all warranties, including the implied warranties of merchantability and fitness for a particular purpose, are excluded. In the event of manufacturing defects in the product, purchasers' remedies are limited to the replacement of the product or the refund of its purchase price. Liability for consequential damages is expressly excluded.

5501-95th Avenue
Kenosha, Wisconsin 53144 USA
1-800-445-1754
www.abatron.com

ISO 9001 Registered. Made in USA.