



Electric Automation
Automation specialists

Reference: T8L3200
Code: 1SDA065734R1

T8L 3200 PR331/P LSI In=3200A 3p F VR

Buy it at [Electric Automation Network](#)



C.BREAKER TMAX T8L 3200 FIXED THREE-POLE WITH TERMINALS REAR VERTICAL AND SOLID-STATE RELEASE IN AC PR331/P-LSI R 3200

Ordering

EAN:	8015644686413
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85362090

Dimensions

Product Net Width:	427 mm
Product Net Height:	382 mm
Product Net Depth:	282 mm
Product Net Weight:	11.7 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	525 mm
Package Level 1 Height:	665 mm
Package Level 1 Length:	695 mm
Package Level 1 Gross Weight:	13.2 kg

Package Level 1 EAN:	8015644686413
----------------------	---------------

Additional Information

Electrical Durability:	3000 cycle 20 cycles per hour
Mechanical Durability:	15000 cycle 60 cycles per hour
Number of Poles:	3
Power Loss:	at Rated Operating Conditions per Pole 117 W
Product Main Type:	SACE Tmax T
Product Name:	Automatic Circuit Breaker
Product Type:	CB
Rated Current (I_n):	3200 A
Rated Impulse Withstand Voltage (U_{imp}):	8 kV
Rated Insulation Voltage (U_i):	1000 V
Rated Operational Voltage:	690 V AC
Rated Service Short-Circuit Breaking Capacity (I_{cs}):	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 85 kA (400 V AC) 85 kA (415 V AC) 85 kA (440 V AC) 85 kA (500 V AC) 65 kA (690 V AC) 50 kA
Rated Short-time Withstand Current (I_{cw}):	for 1 s 40 A
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}):	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 85 kA (400 V AC) 85 kA (415 V AC) 85 kA (440 V AC) 85 kA (500 V AC) 65 kA (690 V AC) 50 kA
Rated Uninterrupted Current (I_u):	3200 A
Release Type:	EL
Standards:	IEC 60947
Sub-type:	T8
Terminal Connection Type:	Fixed Circuit-Breakers Rear flat Vertical
Version:	F

Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	1SDC210023D0201
Declaration of Conformity - CE:	1SDL000165R0008

Classifications

ETIM 4:	EC000228 - Power circuit-breaker for trafo/generator/ installation prot.
ETIM 5:	EC000228 - Power circuit-breaker for trafo/generator/ installation prot.
Object Classification Code:	Q