

APTURA® LT30 Self-Retracting Lanyard

Advanced Performance Technology



MSA has set a new standard in the mechanical fall protection market with the Aptura LT30 Self-Retracting Lanyard (SRL). With its solid design and fast-acting brake mechanism, you can be confident that the Aptura LT30 SRL will be there for you when you need it most.

The Aptura LT30 SRL features include:

- ➔ **A durable, engineered high-impact thermoplastic housing** to increase service life.
- ➔ **Rugged, impact-absorbing protective bumpers** for added durability.
- ➔ **A field-replaceable lifeline option.** In the event that the webbing should become damaged, this option provides a field-replaceable web lifeline, eliminating costly returns to the manufacturer. The Aptura LT30 is the first 30' SRL on the market to offer this feature.
- ➔ **A lightweight design starting at 7.5 pounds**, making it one of the lightest 30' SRL's on the market.
- ➔ **A standard lifeline length of 30'.** Available in lengths from 13' to 30' in 1' increments.

- ➔ **A 400 pound working capacity** as a standard feature.
- ➔ **No annual factory re-certification** required due to high-quality construction. This not only reduces the cost of ownership, but also eliminates down time.
- ➔ **An integral load indicator** lets you know when it is time to remove the product from service.
- ➔ **SRL connector with integral swivel.**
- ➔ **Meets ANSI A10.32, ANSI Z359.1, and all applicable OSHA standards, and is CSA certified.**
- ➔ **ATO ordering flexibility** allows you to order the exact options, and only the options you want.

All these features and more combine to deliver the lightest weight, most versatile SRL available on the market today, the APTURA LT30 self-retracting lanyard.

Aptura LT Self-Retracting Lanyard Assemble-To-Order Matrix

Approval	Line Length	SRL Connector	Lifeline Connector	Field-Replaceable Line
N Non-CSA C CSA	08 13'	00 None	00 None (Sewn Loop)	0 No
	09 14'	01 Back D-ring Connector (P/N 10089205)	01 HL2000 Snaphook (P/N 10002490)	1 Yes
	10 15'	02 1" Aluminum Carabiner (P/N SCRA853)	02 Swivel HL2000 Snaphook (P/N 10023769)	
	11 16'	03 1" Steel Carabiner (P/N 10089207)	03 RL20 Snaphook (P/N 520603)	
	12 17'	04 2" Aluminum Carabiner (P/N SRCA722)	04 Swivel RL20 Snaphook (P/N 520691)	
	13 18'	05 2" Steel Carabiner (P/N 506308)	05 LI Aluminum Snaphook (P/N 10014393)	
	14 19'		06 1" Steel Carabiner (P/N SRCC643)	
	15 20'		07 1" Aluminum Carabiner (P/N SRCA853)	
	16 21'		08 1" Steel Swivel Carabiner (P/N 10021804)	
	17 22'		09 LS Snaphook (P/N SHW5531690LS)	
	18 23'		10 AL64 Snaphook (P/N 10043811)	
	19 24'		11 LS Swivel Snaphook (P/N 10053393)	
	20 25'		12 LS Swivel Snaphook w/ Load Indicator (P/N 10038740)	
	21 26'		13 36C Snaphook (P/N 10088270)	
	22 27'		14 36CS Snaphook (P/N 10089159)	
	23 28'			
	24 29'			
	25 30'			

A-APT							
Part Number							
Quantity							

- ATO orders will ship within 5 days of order
- Products ordered using the ATO system are non-returnable
- Line lengths available from 13' to 30' in 1 foot increments



P/N 10053560

APTURA LT30 SRL Ordering Information

Part No.	Line Length	SRL Connection	Lifeline Connection	Field Replacement Line
10050504	30'	None	LI Snap	Yes
10053558	30'	None	HL2000	Yes
10053559	30'	1" Steel Carabiner	LS Snap	Yes
10053560	30'	1" Steel Carabiner	HL2000	Yes
10088386	30'	None	36C	Yes
10088387	30'	1" Steel Carabiner	36C	Yes
10058886	30'	None	Swivel LS	Yes

APTURA LT30 Lifeline Replacement Kits Ordering Information

Replacement kits include lifeline with nozzle, snap or carabiner per your order, line replacement cover, screw, hex wrench, and square wrench.

Part No.	Description
10054753	Replacement 30' lifeline with HL2000 Snap
10054754	Replacement 30' lifeline with HL2000 Swivel Snap
10054755	Replacement 30' lifeline with RL20 Snap
10054756	Replacement 30' lifeline with RL20 Swivel Snap
10054757	Replacement 30' lifeline with LI Snap
10054758	Replacement 30' lifeline with 1" Steel Carabiner
10054759	Replacement 30' lifeline with 1" Aluminum Carabiner
10054760	Replacement 30' lifeline with 1" Steel Swivel Carabiner
10054771	Replacement 30' lifeline with LS Snap
10054772	Replacement 30' lifeline with LS Swivel Snap
10054773	Replacement 30' lifeline with AL64 Snap
10054774	Replacement 30' lifeline with sewn loop

SRL Connector Options



Attaching the snaphook to the integral swivel creates a comfortable, convenient carrying handle.



1" Aluminum Carabiner

1" Steel Carabiner

LI Snaphook

HL2000 Swivel Snaphook

1" Steel Swivel Carabiner

RL20 Snaphook

AL64 Snaphook

HL2000 Snaphook

LS Snaphook

RL20 Swivel Snaphook

LS Swivel Snaphook

36C Snaphook

LS Swivel Snap with Load Indicator

36CS Snaphook

Lifeline Connector Options

Additional Great Products From MSA

EVOTECH® Full Body Harness

MSA's EVOTECH Full Body Harness offers the latest design features that improve user comfort, ease of use, durability, and user safety.

- No binding edge on shoulder pad to reduce neck chafing
- Breathable padding with moisture-wicking material keeps users cooler
- Patent-pending leg strap design keeps leg straps in place, increasing mobility and comfort
- Dual-color webbing simplifies harness donning
- NanoSphere coating on webbing repels dirt, grease, moisture, etc.
- Meets OSHA regulations, ANSI Z359.1/ANSI A10.32 and CSA Z259.10-06

In addition to the features above, the EVOTECH harness includes patented variable width sub-pelvic webbing which provides 50% more surface area for improved weight distribution, improving comfort during work positioning and personnel riding applications. The EVOTECH harness is also available with Suspension Trauma Safety Step to improve post-fall comfort and help to prevent suspension trauma.



Removable Concrete Anchors

- Quickly and easily removed and reinstalled in another location
- Compact and lightweight
- Durable stainless steel and aluminum construction
- 400 lb capacity
- Available in two models
 - 5,000 lb version (5K)
 - 10,000 lb (10K) version*



*10,000 lb version can be used to anchor MSA Dyna-Line or Sure-Line Horizontal Lifelines

Sure-Stop Shock-Absorbing Lanyards

- Tear-tape design to keep fall arrest forces below 900 lbs
- Restraint lanyards offered in adjustable and fixed lengths
- Available in rope, cable and web
- Models meet OSHA regulations and ANSI A10.32. Some models meet Z359.1-2007 and CSA Z259.11-05.



Note: This bulletin contains only a general description of the products shown. While uses and performance capabilities are described, under no circumstances shall the products be used by untrained or unqualified individuals and not until the product instructions including any warnings or cautions provided have been thoroughly read and understood. Only they contain the complete and detailed information concerning proper use and care of these products.



ID 2300-69-MC / September 2010

© MSA 2010 Printed in U.S.A.

Corporate Headquarters
P.O. Box 426, Pittsburgh, PA
15230 USA
Phone 412-967-3000
www.MSAnet.com

U.S. Customer Service Center
Phone 1-800-MSA-2222
Fax 1-800-967-0398

MSA Canada
Phone 1-800-672-2222
Fax 1-800-967-0398

MSA Mexico
Phone 01 800 672 7222
Fax 52-44 2227 3943

MSA International
Phone 412-967-3354
FAX 412-967-3451

Offices and representatives worldwide

For further information:

MSA
The Safety Company